



Communications Terminal

CT2100

DATA SPEED: [REDACTED] MODE: [REDACTED] <small>9600 4800 ASCII BAUDOT WCRSE</small>		DISPLAY PAGE: [REDACTED] LINE: [REDACTED] STATUS: [REDACTED] REV: [REDACTED] USOS: [REDACTED] CLEAR: [REDACTED] <small>CT2100 C-1000 V-1000 V-1000</small>				TX/RX CONTROL HDZ: [REDACTED] IDEE: [REDACTED] MAN TX: [REDACTED] KDS: [REDACTED] <small>FDX AUTO</small>			MONITOR VOLUME [KNOB] ON OFF
MODEM RTTY HIGH: [REDACTED] NORM: [REDACTED] AUTO: [REDACTED] RTTY SHFT: [REDACTED] <small>MODEM LOW RTTY</small>		TUNING INDICATORS OVD: [REDACTED] MARK: [REDACTED] +/-: [REDACTED] SPACE: [REDACTED] CW: [REDACTED]				I/O AUDIO: [REDACTED] RCVE: [REDACTED] NORM: [REDACTED] <small>RCV-11 TAPS</small>		OUTPUT INFO: [REDACTED]	

The keyboard is a full-sized unit with a dark frame and a light-colored keycap set. It features a standard QWERTY layout with several function keys: IDENT, ESC, CTRL, and SHIFT on the left; and HERE IS, SRK, BUR, and RETURN on the right. The keyboard is mounted on a base that also houses the terminal's control panel.